



syn1588®

syn1588® PCIe NIC - Revision 2

Brief Data Sheet


Version 2.1 – March 2017

Features

- 10/100/1000 Mbit Ethernet network interface card
- Green Ethernet support IEEE 802.3az
- PCI Express card (half height)
 - PCI Express V2.0 mode with 5 Gbit/s lane speed
- IEEE1588-2002 & IEEE1588-2008 compliant
- Master and Slave capable PTP Node (with syn1588® PTP Stack)
- IEEE1588 hardware timestamping
- Patented on-the-fly timestamping (1-step mode)
- Clock accuracy up to ± 4 ns
- syn1588® PTP Stack binary run-time license included (Linux & Windows)
- Up to 4 programmable I/O signals available on SMA jacks
- Connectivity to an external GPS receiver via the 1PPS input and RS232 port of the host PC
- Drivers for Linux & Windows
- User configuration, remotely upgradeable

Options

- Timestamping of arbitrary packets via user configurable packet filter engines
- Oscillator option: OCXO
- 1000BASE-X (fiber) mode using SFP type interface
- **New with revision 2.1**
External clock input driving the syn1588® clock signal



syn1588® PCIe NIC Revision 2

The syn1588® PCIe NIC is a standard 10/100/1000 Mbit PCI Express Ethernet network interface card with enhancements to provide highly accurate clock synchronization via the IEEE1588 standard. The syn1588® PCIe NIC provides all real-time functions required for an IEEE1588 node to operate both in master and slave mode.

The syn1588® PCIe NIC comes with the network driver and a run-time license of the syn1588® PTP Stack. The latter performs all IEEE1588 tasks like master/slave selection via the best master clock algorithm. Both driver and stack are available for Linux and Windows.

Furthermore, the syn1588® PCIe NIC may operate either in 2-step or 1-step PTP mode using Oregon Systems' patented on-the-fly time stamping technique for the latter mode.

The syn1588® PCIe NIC is capable of handling up to four high accuracy digital IO signals directly linked to the high accuracy clock within the FPGA device. The direction and functions of these I/O signals may be selected by the user via a remote configuration interface. The options for these signals are:

- **1PPS output** A rising edge is generated once every second.
- **1PPS input** Used to link to an external GPS timing receiver that supplies absolute time reference for grand master applications.


- **EVENT input** A signal transition of an external signal (e.g. a sensor value reaching a threshold) will be time stamped using the high accuracy clock.
- **TRIGGER output** A single event (change of signal state) at a programmable time derived from the high accuracy clock a trigger signal is generated.
- **PERIOD output** An arbitrary, user selectable frequency derived from and phase locked to the high accuracy clock with a resolution of 0.0001 Hz may be generated
- **IRIG-B output** Optionally an IRIG-B000 output signal is generated instead of the 1PPS signal.

The syn1588® PCIe NIC offers two additional user configurable packet filter engines allowing to generate highly accurate time stamps upon receiving or transmitting of an arbitrary class of Ethernet messages.

New with Revision 2

The native PCIe interface supports PCIe version 2.0 (5 Gbit/s) with improved access times that will increase the accuracy for synchronizing the host PC's local clock. Additionally, the syn1588® PCIe NIC now supports Green Ethernet (IEEE802.3az).

The default oscillator is now a TCXO. Optionally, the card is available with a 1000BASE-X fiber interface (SFP type). An on-board high performance analog PLL allows generation of synchronized, high quality single ended clock frequencies up to 156.25 MHz.



syn1588®

syn1588® PCIe NIC – Revision 2

Brief Data Sheet

Version 2.1 – March 2017

Technical Specifications	
Standards	IEEE802.3-2008 IEEE802.3az Energy-Efficient Ethernet IEEE802.1Q Virtual Bridged Local Area Networks IEEE1588-2002 Precision Time Protocol IEEE1588-2008 Precision Time Protocol PCI Express interface & signaling V1.1a and V 2.0
Installable PCI slot	PCI Express 1/2/4/8/16 lane slot
Supported functions	Programmable hardware timestampers IEEE1588 compatible high precision hardware clock Up to 4 programmable SMA I/Os
Storage temperature	-40°C to 85°C
Operating temperature	0°C to 50°C
Humidity	5% to 80% non-condensing
Dimension	135 x 66,4 mm Half height PCI card with bracket (three bracket options available)
Driver support	Linux kernel version 2.6.16 to 3.14 Microsoft Windows XP Microsoft Windows Server 2003 (32/64 bit) Microsoft Windows Server 2008 (32/64 bit) Microsoft Windows 7 (32/64 bit)



The Flavour of Excellence

Franzosengraben 8

A-1030 Vienna

Austria

<http://oregano.at>

contact@oregano.at

Copyright © 2017

Oregano Systems – Design & Consulting GmbH

ALL RIGHTS RESERVED.

Oregano Systems does not assume any liability arising out of the application or use of any product described or shown herein nor does it convey any license under its patents, copyrights, or any rights of others.

Licenses or any other rights such as, but not limited to, patents, utility models, trademarks or tradenames, are neither granted nor conveyed by this document, nor does this document constitute any obligation of the disclosing party to grant or convey such rights to the receiving party.

Oregano Systems reserves the right to make changes, at any time without notice, in order to improve reliability, function or design. Oregano Systems will not assume responsibility for the use of any circuitry described herein.

All trademarks used in this document are the property of their respective owners.