



syn1588[®] Software Suite

Release Overview

Version 1.14.2 – January 12th 2022

Oregano Systems – Design & Consulting GesmbH

Franzosengraben 8, A-1030 Vienna

P: +43 (676) 84 31 04-300

@: contact@oregano.at

W: <http://oregano.at>

1 Legals

Copyright © 2022 Oregano Systems – Design & Consulting GesmbH

ALL RIGHTS RESERVED.

Oregano Systems does not assume any liability arising out of the application or use of any product described or shown herein nor does it convey any license under its patents, copyrights, or any rights of others.

Licenses or any other rights such as, but not limited to, patents, utility models, trademarks or tradenames, are neither granted nor conveyed by this document, nor does this document constitute any obligation of the disclosing party to grant or convey such rights to the receiving party.

Oregano Systems reserves the right to make changes, at any time without notice, in order to improve reliability, function or design. Oregano Systems will not assume responsibility for the use of any circuitry described herein.

All trademarks used in this document are the property of their respective owners.

2 Contents

v1.14 2021-Q4	3
Skipped 2021-Q3	4
v1.13 2021-Q2	4
Skipped 2021-Q1	5
Skipped 2020-Q4	5
v1.12 2020-Q3	6
v1.11 2019-Q4	6
v1.10 2019-Q3	7
v1.9 2019-Q2	7
v1.8 2019-Q1	7
Further Information	9

v1.14 2021-Q4

Overview

This release focuses on the integration of a new log system for the syn1588® Software Suite and further streamlining of the syn1588® PCIe NIC and Dual NIC Linux module for Linux.

New Logger

The new PTP logger is a complete re-work of the existing logging class. The new default implementation utilizes the libfmt library v8.0.1 which provides a rich feature-set for formatting log output and is part of the C++ Standard 2020.

With this new logger a connection (“log sink”) to common OS loggers has been added. The Event Logger for Windows OS and syslog for Linux OS.

You can find a detailed description in the new document “syn1588_upcoming_changes”, which also includes a roadmap and migration recommendations for moving from the old to the new logger.

Linux module: syn1588® technology, PCIe NIC, Dual NIC

The syn1588® technology, which incorporates the syn1588® Software Suite, can also be applied to non-standard systems (SoC FPGAs) that are Linux based. The Linux module has been generalized to better support devices utilizing a device tree (SoC FPGAs).

The Linux module has been generalized to better support devices utilizing a device tree (SoC FPGAs).

This update also adds

- A basic PHC interface to the syn1588® hardware clock, this feature will be extended in future releases
- A module parameter to configure a syn1588® Dual NIC to use a common hardware clock for both interfaces or two independent hardware clocks (default)
- A module parameter to silence the SMA outputs of a syn1588® PCIe Single NIC or Dual NIC

Redundant Clock Synchronization Update

The syn1588® utility redSync can now utilize a syn1588® PCIe Dual NIC for redundant synchronization to two PTP Leaders. For this support, a kernel module parameter can be used to configure the two Dual NIC interfaces to use a common hardware clock.

Quality of life improvements

- The syn1588® Linux module is now available as rpm package for easier installation and maintenance in RedHat and CentOS based Linux systems
- A syn1588® Linux module kernel parameter can be used to silence the SMA outputs at system start
- The syn1588® Software Suite components started as Windows service can now be accessed via the shared memory API from a user application. This is disabled by default. Refer to AN021 for more information.

Skipped 2021-Q3

Due to issues found in the internal regression tests, we decided to skip this release window.

v1.13 2021-Q2

Overview

This release focuses on PTP v2.1 and quality of life improvements throughout all components of the syn1588® Software Suite. Especially interesting for source code customers is the new, state-of-the-art build environment based on cMake and the shift to C++ 2011. Especially interesting for Windows and Linux platform integrators are the different installation packages for easier setup and maintenance of the syn1588 Software Suite.

PTP v2.1

With the release of the new IEEE1588 standard specifying PTP v2.1 we have been busy implementing and extending the support of the syn1588® PTP Stack.

In this release you get access to PTP v2.1 for early exploration. We are currently testing different scenarios and use-cases of PTP v2.1 and PTP v2.0 interoperability and target the next release (Q3 2021) for finalizing PTP v2.1 support.

You can find a detailed list of PTP v2.1 options targeted for future releases in the syn1588® Release Roadmap. If you require specific features, please contact us, so we can integrate your request in the roadmap.

Redundant Clock Synchronization Update

We introduced the syn1588® utility redSync with release v1.12.

The current release features an extension to this utility, providing redundant synchronization of the system clock. It operates together with the syn1588® ISync utility and two physical interfaces (either syn1588® PCIe NIC or other IEEE1588 capable interfaces).

Quality of life improvements

- The syn1588® Software Suite is now available as Debian package for installation in Linux systems and as package for simpler installation in Windows systems
- The syn1588® PCIe NIC and Dual NIC Linux module is now available as Debian package for easier installation and maintenance in Linux systems
- Updated and added configuration files for all supported PTP profiles

New features

- syn1588® utilities and PTP Stack can now select the syn1588® hardware by clockID
- Explicit syn1588® hardware time stamper selection, this allows users high-level access to the different timestamping units of the syn1588® technology

For current and future source code customers

cMake build environment

The switch from the old, proprietary build environment to industry standard cMake will allow faster and friction less integration of the syn1588® software suite into existing and new projects and improve the syn1588® software suite release cycle.

C++ 2011 language standard

C++ 2011 support has been available for almost 8 years for both GCC (4.8.1) and Visual Studio (2013), Hence, we are incrementally adding C++ 2011 language features in our rework of the syn1588® software suite libraries.

Skipped 2021-Q1

Due to big changes to the internal structure of the syn1588 code base and build environment, we decided to skip this release.

You will find these and other improvements in the release scheduled for 2021-Q2.

Skipped 2020-Q4

Due to big changes to the internal structure of the syn1588 code base and build environment, we decided to skip this release.

You will find these and other improvements in the release scheduled for 2021-Q2.

v1.12 2020-Q3

Overview

This release focuses on redundant PTP clock synchronization and introduces the redSync utility for this mode. In addition, a new Linux driver for the syn1588® PCIe NIC is introduced which is compatible with the current syn1588® PCIe NICs as well as the brand new syn1588® Dual NIC.

redSync utility

This new utility allows the user to run two syn1588® PTP stack instances in parallel. Each synchronizing with a different PTP Master over a common syn1588® PCIe NIC interface. This utility can be configured to use the first syn1588® PTP stack that is in-sync with its PTP Master or to compare both syn1588® PTP Stacks (and their Masters) via the PTP BMCA and select the better PTP Master. The utility will monitor both syn1588® PTP stacks during operation. It will seamlessly switch to the backup syn1588® PTP Stack when the primary syn1588® PTP Stack connection or the quality of its PTP Master degrades.

Take a look at the syn1588® User Guide for a detailed overview of the redSync utility and its recommended application or contact Oregano Systems (contact@oregano.at or sales@oregano.at) for more details.

syn1588 PCIe NIC driver for Linux

We introduce the new syn1588® PCIe NIC driver for Linux which provides the usual support for the syn1588® PCIe NIC. In addition, this driver supports the brand new syn1588® Dual NIC, i.e., one will be able to use both ports of the syn1588® Dual NIC like the well-known syn1588® PCIe NIC. This will allow you a seamless integration of the syn1588® Dual NIC in your current applications. Upcoming releases will incrementally introduce advanced features of the syn1588® Dual NIC. This driver directly replaces the current syn1588® PCIe NIC driver.

v1.11 2019-Q4

Overview

This release focuses on documentation of the user APIs. In addition, preparations for redundant clock synchronization have been added to the software suite. This involves

- access to a second timestamping unit on the same interface of a syn1588® PCIe NIC device
- enabling/disabling control of the clock for a PTP Stack

v1.10 2019-Q3

Overview

This release focuses on 32-Bit and 64-Bit system compatibility. It further includes improvements to the PTP Security implementation and various bugfixes and smaller improvements.

v1.9 2019-Q2

Overview

The 2019 v1.9 Release of the syn1588® software suite is mostly concerned with increasing the performance and the improvement of our documentation. The new feature introduced with this release is an implementation of the PTP v2.1 Security protocol, which is described below.

PTPv2.1 Security

The first feature from the upcoming PTP Version 2.1 implements the PTP Security protocol as specified in IEEE1588-2018. The PTP Security protocol provides an effective way to secure PTP traffic from Man-In-The-Middle attacks, Replay attacks as well as malicious Master spoofing. See the Application Note *an_security.pdf* for further details.

v1.8 2019-Q1

Overview

The most interesting improvement introduced with the Q1-2019 release of the syn1588® Live System is the new feature Dynamic Port Re-configuration, which will be described below. Apart from that, the current release features a couple of minor bugfixes relating to different parts of the syn1588® software, such as the parser, offset compensation, and improvements in the handling of Layer2 mode.

Dynamic Port Re-configuration

The Precision Time Protocol has introduced the concept of PTP ports. During start-up of the syn1588® PTP Stack a physical port is linked to a PTP port. In previous versions of the syn1588® PTP Stack this was done statically. Any changes in the physical port required to stop the syn1588® PTP stack and re-invoke it after making the changes for the Ethernet port

Dynamic Port Re-configuration allows to user to modify the Ethernet port (i.e. change the IP Address) or link a different Ethernet port to a specific PTP port) during runtime of the syn1588® PTP Stack. The reconfiguration is done via the Shared Memory API.

For further information on how to use the Dynamic Port Re-configuration feature, please take a look at the example program in the Shared Memory API export.

Further Information

You are looking for further information about our syn1588® product line-up? Please contact Oregano Systems support! We will be pleased to provide you all the required information.



Franzosengraben 8

A-1030 Vienna

AUSTRIA

<https://www.oreganosystems.at/>

support@oregano.at